



- Alternating current (AC) MMA electrode welding machine, 250A. Three-phase, 400V power supply. On wheels.
- Usable electrodes: rutile up to 5 mm.
- Continuous adjustment of welding current.
- Thermostatic protection.

## TECHNICAL DATA

CODE	<b>812011</b>	MAX CURRENT AC EN60974-1	<b>200 @ 10 % A</b>	POWER FACTOR(cosphi) (cosphi)	<b>0,55</b>
SINGLEPHASE MAINS VOLTAGE	<b>230 V</b>	AC CURRENT AT 60%	<b>70 A</b>	D.USABLE ELECTRODES AC	<b>2 - 5 mm</b>
TWO-PHASE MAINS VOLTAGE	<b>400 V</b>	MAX NO LOAD VOLTAGE IN AC	<b>55 V</b>	PROTECTION DEGREE	<b>IP21</b>
MAINS FREQUENCY	<b>50 / 60 Hz</b>	MAX ABSORBED POWER	<b>8,5 kW</b>	DIMENSIONS (LxWxH)	<b>75 x 36 x 49 cm</b>
CURRENT RANGE IN AC	<b>70 - 250 A</b>	ABSORBED POWER AT 60%	<b>2,6 kW</b>	WEIGHT	<b>25 kg</b>

## ON REQUEST ACCESSORIES

### ACCESSORIES/VARIOUS/SPARE PART

801096 MMA WELDING KIT 200A 16 MMQ 3+2M AX25

## DESCRIPTION

MMA stick electrode welding machine in alternating current (AC).  
 Stepless regulation of welding current.  
 With thermostatic protection.  
 Use with a wide range of electrodes: rutile.

## DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



CERTIFICATE