



- Alternating current (AC) MMA electrode welding machine, 250A. Three-phase, 400V power supply. On wheels.
- The model has secondary dual voltage and can also weld basic and rutile electrodes up to 5mm.
- Continuous adjustment of welding current.
- Thermostatic protection.

TECHNICAL DATA

CODE	817017	MAX CURRENT AC	320 @ 15 % A	D.USABLE ELECTRODES AC	2 - 6 mm
SINGLEPHASE MAINS VOLTAGE	230 V	AC CURRENT AT 60%	170 A	PROTECTION DEGREE	IP22
TWO-PHASE MAINS VOLTAGE	400 V	MAX NO LOAD VOLTAGE IN AC	52 - 73 V	DIMENSIONS (LxWxH)	83 x 45,5 x 58 cm
MAINS FREQUENCY	50 / 60 Hz	MAX ABSORBED POWER	13 kW	WEIGHT	61 kg
CURRENT RANGE IN AC	70 - 350 A	ABSORBED POWER AT 60%	4,5 kW		
MAX CURRENT AC EN60974-1	215 @ 35% A	POWER FACTOR(cosphi) (cosphi)	0,4		

ON REQUEST ACCESSORIES

ACCESSORIES/VARIOUS/SPARE PART

801081 MMA WELDING KIT 300A 25 MMQ 4+3M AX50

DESCRIPTION

MMA stick electrode welding machine in alternating current (AC).

Stepless regulation of welding current.

With thermostatic protection.

The model has double secondary voltage for use also with basic and rutile electrodes.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



CERTIFICATE