

PULSE 30 EVO



- Multi-functional electronic battery charger, trickle charger and tester for WET, GEL, AGM, MF, PbCa, EFB, Li 12/24V batteries with LCD screen.
- Automatic charging and trickle charging in Pulse Tronic based on the technology of the selected battery.
- Advanced functions: BOOST for rapid charging; COLD for charging and trickle charging of batteries at low temperatures; TEST alternator, cranking and charging status of the battery; RECOVERY to recover sulphated batteries; SUPPLY for continuous and reliable power supply during battery changes.
- Contained size and weight. Designed for wall hanging.
- Safety guaranteed by protection against overcharging, short circuit and pole inversion.
- Cable with clamps.



TECHNICAL DATA

CODE	807610	EFFECTIVE CHARGING CURRENT	27 / 15 A	PROTECTION DEGREE	IP33
SINGLEPHASE MAINS VOLTAGE	230 V	RATED CHAR.CUR.EN60335-2-29	25 / 12 A	DIMENSIONS (LxWxH)	9,2x20x33 cm
MAINS FREQUENCY	50 / 60 Hz	QUICK CHARGE/START CURRENT	25 (Boost) A	WEIGHT	3,11 kg
CHARGING ABSORBED POWER	369 W	MIN.RATED REFERENCE CAPAC.	5 Ah		
CHARGING VOLTAGE	12 / 24 V	MAX.RATED REFERENCE CAPAC.	400 Ah		

SUPPLIED ACCESSORIES

125277 CLAMPS PATCH CORD

ON REQUEST ACCESSORIES

OTHER CHARGING/STARTING ACCESS		
803086	HOLDING BRACKET KIT	
803087	MAGNET KIT	

DESCRIPTION

Multi-functional electronic battery charger, trickle charger and tester for WET, GEL, AGM, MF, PBCA, EFB, Li 12V/24V batteries with LCD display.

Charging and maintenance programs in Pulse Tronic dedicated to the technology of the selected battery. BOOST function for quick charge. Advanced function for charging and maintenance of batteries at low temperatures. Activation of the RECOVERY function enables resetting of sulphated batteries. Tests the vehicle alternator and battery. Continuous and reliable power supply source during battery changes. Simplified use and immediate display of the parameters thanks to the LCD display.

Features:

- Automatic charge and maintenance in Pulse Tronic based on the technology of the selected battery;
- BOOST function for quick charge of the batteries;
- COLD function to charge and maintain batteries at low temperatures;
- RECOVERY function to recover sulphated batteries;
- TEST function for battery, starting and alternator;
- SUPPLY function for stable power supply during battery changing;
- LCD display;
- Battery voltage selection;

- Protection against overcharge, short circuit and polarity reversal.

Fit with PFC device.

Complete with cables with clamps.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL