



- Battery manager for complete maintenance and rapid cranking of 12V/24V WET, GEL, AGM, MF, PbCa, EFB and Li batteries. 570A start max. With LCD screen.
- Automatic charging and trickle charging in Pulse Tronic based on the technology of the selected battery.
- Battery test, cranking and alternator; regeneration and recovery of batteries; source of stable power supply for battery changes; cranking.

TECHNICAL DATA

| | | | | | |
|---------------------------|-------------------|-----------------------------|------------------|----------------------------|----------------------------|
| CODE | 829342 | CHARGE AND STARTING VOLTAG. | 12 / 24 V | MIN.RATED REFERENCE CAPAC. | 10 Ah |
| SINGLEPHASE MAINS VOLTAGE | 230 V | EFFECTIVE CHARGING CURRENT | 90 A | MAX.RATED REFERENCE CAPAC. | 1550 Ah |
| MAINS FREQUENCY | 50 / 60 Hz | RATED CHAR.CUR.EN60335-2-29 | 70 A | DIMENSIONS (LxWxH) | 36,5 x 46 x 75,5 cm |
| CHARGING ABSORBED POWER | 2 kW | START CUR.1V/C EN60335-2-29 | 360 A | WEIGHT | 23,4 kg |
| STARTING ABSORBED POWER | 10 kW | MAX STARTING CURRENT | 570 A | | |

ON REQUEST ACCESSORIES

| BATTERY CHARGERS FUSES | |
|------------------------|-------------------|
| 802029 | FUSES 100A 20 PCS |

DESCRIPTION

Multifunction, electronic battery charger, starter and tester (BATTERY MANAGER), for WET, GEL, AGM, MF, PbCa, EFB and Li batteries at 12V/24V.

It grants complete maintenance of batteries and quick starting of cars, vans and light trucks.

It is an indispensable tool for stable power supply during battery changes.

Easy and intuitive to use thanks to the graphical LCD screen.

Features:

- Automatic charging and maintenance in Pulse Tronic;
- Battery, start and alternator test;
- Regeneration and recovery of batteries;
- Stable power source for battery changes (safeguard of the on-board electronics);
- Starting of all types of cars, vans, light trucks.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



CERTIFICATE