

**HA**

**T.S.** Total Stop



**1450**  
RPM



**STANDARD EQUIPMENT**

- 3.700.0036 Gun M22 - 3/8



- 3.701.0027 Lance M22 high/low pressure



- 3.103.0050 Nozzle type 045 (mod. 1311 LP)
- 3.103.0047 Nozzle type 030 (mod. 1510 LP)



- 4.618.0049 High pressure hose 8 m



- Power cable 5 m

**Equipped with:**

- 4 poles electrical motor (1450 RPM) with thermal protection.
- Three ceramic coated pistons, brass linear pump head with built-in by-pass valve.
- Suction and delivery S. S. valves.
- Detergent built-in tank for indirect suction.
- Pressure regulator.
- Glycerine pressure gauge.
- Accessory holder.
- Hose-holder.
- Ergonomic handle.
- 7,5 l detergent tank.

|                              | HA 1311 LP                  | HA 1510 LP                  |
|------------------------------|-----------------------------|-----------------------------|
| code                         | 8.665.0117                  | 8.665.0122                  |
| operat. pressure/max         | 130/150 bar-1885/2175 psi   | 150/160 bar-2175/2320 psi   |
| delivery rate                | 660 l/h-2.90 GPM            | 600 l/h-2.64 GPM            |
| abs. power/voltage           | 2900W - 230V~50Hz 1 ph      | 2900W - 230V~50Hz 1 ph      |
| motorpump type/RPM           | MP3/1450 RPM                | MP3/1450 RPM                |
| max. water inlet temperature | 40 °C                       | 40 °C                       |
| dimension/weight             | 59x37x87cm / 28 Kg - 61 lbs | 59x37x87cm / 28 Kg - 61 lbs |