

## GV Kone

8.404.0051



### Standard equipment:

- Hose 2,8 m 
- 2x 6.402.0078 
- 6.402.0003 
- 6.402.0004 
- 6.402.0006 
- 6.402.0005 
- 6.402.0040 
- 6.402.0009 
- 3.099.1053 
- 3.099.1052 
- 3.099.0126 
- 3.099.0189 
- 0.010.0028 Antiscale sachet 50gr



## GV Kone

### Technical data sheet

### المواصفات الفنية

#### Motor and pump specifications:

#### مواصفات الماتور والطمبة:

- 1) Heating and activation time required: 10 min.
- 2) Double thermostat for fast temperature sensing.
- 3) A technical mechanical cover for easy closing and opening.
- 4) Cap with protection against anti-unscrewing and safety valve.

- ١) يتم التسخين وبدء العمل بعد ١٠ دقائق من بدء التشغيل عند أول استخدام.
- ٢) ترموستات مزدوجة لسرعة الاستشعار بالحرارة.
- ٣) غطاء ميكانيزم فني لسهولة الغلق والفتح.
- ٤) الماكينة مزودة بغطاء حماية ويحتوي على بلف أمان عند ارتفاع الضغط بالسخان.

#### Accessories:

#### الكماليات:

- 1) Power cable holder.
- 2) Control panel with lamps includes:
  - a. Steam sensor lamp.
  - b. Water shortage lamp with heater.
- 3) Steam regulator.
- 4) Thermometer.
- 5) Power cable 6 m.
- 6) The machine is loaded on wheels for easy movement.

- ١) مزودة بحامل كابل كهربائي.
- ٢) مزودة ببلوحة تحكم مضيئة تشمل الآتي:
  - لمبة عند استشعار البخار.
  - لمبة عند نقص المياه بالسخان.
- ٣) بكرة تحديد كمية البخار.
- ٤) عداد الحرارة.
- ٥) كابل كهرباء بطول ٦ م.
- ٦) الماكينة محملة على عجل لسهولة الحركة.

#### Technical Specifications:

#### المواصفات الفنية:

- 1) **Operating current:** 220 V - 50 Hz - 1 ph.
- 2) **Motor power:** 2300 W.
- 3) **Pressure:** 4 bar.
- 4) **Water temperature:** 143° C.

- ١) **تيار التشغيل:** ٢٢٠ فولت - ٥٠ هرتز - ١ فاز.
- ٢) **قدرة الماتور:** ٢٣٠٠ وات.
- ٣) **الضغط:** ٤ بار.
- ٤) **درجة حرارة البخار:** ١٤٣ درجة.

### GV Kone



#### Equipped with:

- Saturated steam at 4 bar at a temperature of 143°C
- Boiler 2,3 kW
- Heating and activation time required: 10 min
- Pressure switch
- Double thermostat
- Cap with protection against anti-unscrewing and safety valve
- Handy accessory compartment with electric cable holder
- Control panel with lamps
- Impact resistant covers
- Steam regulation
- Thermometer
- Power cable 6 m.

#### Standard equipment:

- Hose 2,8 m 
- 2x 6.402.0078 
- 6.402.0003 
- 6.402.0004 
- 6.402.0006 
- 6.402.0005 
- 6.402.0040 
- 6.402.0009 
- 3.099.1053 
- 3.099.1052 
- 3.099.0126 
- 3.099.0189 
- 0.010.0028 Antiscale sachet 50gr

#### GV Kone

Code	<b>8.404.0051</b>
Max steam pressure/temperature	4 bar/143° C
Boiler absorbed power	2300 W/220-240V ~ 50Hz
Steam production	80 kg/h max
Boiler type/volume	Alluminium/2,4 l



Lavor steam cleaner GV Kone sanitizes and sterilizes every surface with steam power, without using detergents or disinfectants. GV Kone is environmental friendly.

Steam regulation allows washing adjusting considering the surface to be treated: in this way every kind of surface has the right treatment.



The machine is user friendly and has a wide range of accessories: GV Kone is a comfortable and safe daily working tool.

Steam cleaning function is perfect in shops, premises, offices as well as in household application and removes the toughest and hidden dirt while eliminating mites, germs and bacteria.

