

# Air operated pump for grease without accessories - ratio 50:1



**Codice: 502/N**



For drum 200 kg. Without accessories. Pneumatic working: double acting. Suitable to petroleum based greases NLGI0, NLGI1, NLGI2, NLGI3. To put directly on the grease drum. RATIO 50:1. Nominal flow-rate 2,80 kg/min. Grease exit pressure 400 bar

<b>Body diameter</b>	65 mm
<b>Color</b>	BLACK
<b>Compressed air consumption</b>	150 lt/min (press.: 8 bar)
<b>Compressed air pressure</b>	Max 10 bar
<b>External shank diameter</b>	Ø 28 mm
<b>Flow-rate</b>	1,50 KG/MIN
<b>Frequency of strokes per minute</b>	0÷150
<b>Material</b>	STEEL - BODY: IN ALUMINIUM, SLEEVE: IN BRASS, PUMP ASSEMBLY: IN STEEL, PISTON: IN NBR-RUBBER AND VITON, SEALS: IN NBR-POLYURETANE

<b>Notes</b>	We recommend to use the pressure regulator art.516 to avoid condense that could freeze and obstruct the discharge of the pump.
<b>Operating pressure</b>	400 bar
<b>Operating temperature</b>	10÷ 40°C
<b>Origin</b>	MADE IN ITALY
<b>Pneumatic piston diameter</b>	Ø 60 mm
<b>Ratio</b>	50:1
<b>Regulations</b>	2006/42/CE
<b>Shank length</b>	950 mm
<b>Single packing</b>	CARTON BOX
<b>Suitable for</b>	DRUM 200 KG.
<b>Type</b>	RATIO 50:1
<b>Working</b>	PNEUMATIC

## Accessori disponibili



**Pistola per grasso con accessori**  
Codice articolo: **503**



**Tubo in gomma R.2 per grasso (lungh.3 mt.)**  
Codice articolo: **504**



**Tubo in gomma R.2 per grasso (lungh.5 mt.)**  
Codice articolo: **505**



**Tubo in gomma R.2 per grasso (lungh.7 mt.)**  
Codice articolo: **506**



**Coperchio per fusti 200 kg**  
Codice articolo: **509**



**Premigrasso con membrana per fusti 200 kg**  
Codice articolo: **514**



**Regolatore di pressione**  
Codice articolo: **516**



**Giunto girevole dritto**  
Codice articolo: **520/A**



**Giunto girevole triplo**  
Codice articolo: **522/A**



**Carrello per fusti 200 kg**  
Codice articolo: **572**