

Air operated pump for oil without accessories - ratio 3:1



Codice: 552/N



For drum 200 kg. Without accessories. Pneumatic working: single acting. Suitable to oil SAE 0/40 and SAE 90. To put directly on the oil drum. The pump should be fixed on the drum with the ring (art.559 accessory included). RATIO 3:1. Nominal flow-rate 24 lt/min. Exit oil pressure 24 bar.

Allowed fluids	OIL SAE 0/40, SAE 90
Body diameter	65 mm
Color	BLACK
Compressed air consumption	250 lt/min (press.: 8 bar)
Compressed air pressure	Max 10 bar
External shank diameter	Ø 40 mm
Flow-rate	14 LT/MIN
Material	STEEL - BODY: IN ALUMINIUM, SLEEVE: IN BRASS, PUMP ASSEMBLY: IN STEEL, PISTON: IN NBR-RUBBER AND VITON, SEALS: IN NBR-POLYURETANE

Notes	We recommend to use the pressure regulator art.516 to avoid condense that could freeze and obstruct the discharge of the pump.
Operating pressure	24 bar
Operating temperature	10÷40 °C
Origin	MADE IN ITALY
Pneumatic piston diameter	Ø 35 mm
Ratio	3:1
Regulations	2006/42/CE
Shank length	950 mm
Single packing	CARTON BOX
Suitable for	DRUM 200 KG.
Type	RATIO 3:1
Working	PNEUMATIC

Accessori disponibili



Regolatore di pressione

Codice articolo: **516**



Pistola per olio (con tubo rigido antigoccia)

Codice articolo: **553**



Pistola per olio con contalitri e beccuccio rigido

Codice articolo: **555/C**



Tubo in gomma R.1 per olio (lungh.3 mt.)
Codice articolo: **556**