

FALL ARRESTOR DEVICE WITH BELT STRAP

Light fall arrestor device for universal use in areas with a falling hazard



| | |
|---|---------------------|
| Art. No. | 0899 032 908 |
| P. Qty. | 1 |
| EN standard | 360 |
| Total length of connection element | 2.5 m |
| Width x height x depth | 110 x 110 x 80 mm |
| Weight | 1.13 kg |

FALL ARRESTER DEVICE PRO WITH STEEL CABLE

Offers optimum freedom of movement and flexibility during work whilst providing maximum safety in the event of a fall.



<STEPREF
A="AT_Pic-
tureCaption"
AR="ASSET_
Pictogram"

- Self-retracting steel cable for optimum safety
- In the event of a fall, the device blocks the movement starting from a fall rate of 1.5 m/s
- Robust plastic housing
- Rotary swivel carabiner prevents cable twisting
- Suitable for horizontal applications
- Tested on sharp edges

| Art. No. | 0899 032 120 | 0899 032 121 | 0899 032 122 |
|-------------------------------|---------------------|---------------------|---------------------|
| P. Qty. | 1 | 1 | 1 |
| EN standard | 360 | 360 | 360 |
| Wire cable length | 5 m | 10 m | 15 m |
| Wire cable diameter | 4.8 mm | 4.8 mm | 4.8 mm |
| Width x height x depth | 145 x 210 x 70 mm | 180 x 275 x 80 mm | 265 x 375 x 100 mm |
| Weight | 2.6 kg | 3.76 kg | 5.47 kg |

| | |
|---|---------------------|
| Related products | Art. No. |
| Anchor point set for fall arrestor device | 0899 032 909 |