





**Technical information:**

THE HH VERTICAL PLATE LIFTING CLAMP IS HIGHLY EFFICIENT AUXILIARY LIFTING PRODUCT.

- Meets the WLL performance requirements of BS EN 13155.
- Black color finish.
- Especially hardened jaws for extra durability.
- Lifting under 20% of the rated capacity loading is strictly forbidden.
- Overloading is not permitted.
- The Steel plate lifted should be under the HRC 37 (HB 345).
- The HH Clamp is designed to lift one plate at a time
- Always ensure the operator has access to operating instructions.

TECHICAL DIMENSION	ProductCode	Capacity	JawOpening	T	U	V	L	Weight
		(Kgs)	(mm)	(mm)	(mm)	(mm)	(mm)	(Kgs)
	JCD0.8T	800	0-16	123	265	40	44	2.8
	JCD1T	1000	0-22	124	295	50	54	3.6
	JCD2T	2000	0-30	154	385	54	56	5.5
	JCD3T	3000	0-40	180	400	60	72	10
	JCD5T	5000	0-50	222	483	68	76	17
	JCD8T	8000	0-60	265	535	65	90	26
	JCD10T	10000	0-90	290	600	80	95	32
	JCD12T	12000	60-125	408	700	80	113	48