



- Direct current (DC) MMA electrode welding machine, 320A. Three-phase, 230/400V power supply. On wheels.
- Usable electrodes: rutile, basic, stainless steel, cast iron, etc. up to 6 mm.
- Continuous adjustment of welding current.

TECHNICAL DATA

CODE	819020	MAX CURRENT DC	320 @ 25 % A	POWER FACTOR(cosphi) (cosphi)	0,6
THREEPHASE MAINS VOLTAGE	230 / 400 V	DC CURRENT AT 60%	180 A	D.USABLE ELECTRODES IN DC	2 - 6 mm
MAINS FREQUENCY	50 / 60 Hz	MAX NO LOAD VOLTAGE IN DC	65 V	PROTECTION DEGREE	IP22
CURRENT RANGE IN DC	60 - 320 A	MAX ABSORBED POWER	11,5 kW	DIMENSIONS (LxWxH)	89 x 46 x 59 cm
MAX CURRENT DC EN60974-1	260 @ 35 % A	ABSORBED POWER AT 60%	7 kW	WEIGHT	80 kg

ON REQUEST ACCESSORIES

GOUGING ACCESSORIES

802666 GOUGING KIT

ACCESSORIES/VARIOUS/SPARE PART

801095 MMA WELDING KIT 350A 35 MMQ 4+3M AX50

DESCRIPTION

MMA, rectified, electrode welding machine in direct current (DC).

Stepless regulation of welding current.

Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron and aluminium.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



CERTIFICATE