



- Direct current (DC) MMA electrode welding machine, 360A. Three-phase, 230/400V power supply. On wheels.
- Usable electrodes: rutile, basic, stainless steel, cast iron, aluminium, etc. up to 6 mm.
- Continuous adjustment of welding current.
- For heavy applications. With eyebolts for movement on the ship building site.
- Optional gouging kit.

TECHNICAL DATA

CODE	819090	DC CURRENT AT 60%	240 A	D.USABLE ELECTRODES IN DC	2 - 6 mm
THREEPHASE MAINS VOLTAGE	230 / 400 V	MAX NO LOAD VOLTAGE IN DC	62 V	PROTECTION DEGREE	IP22
MAINS FREQUENCY	50 / 60 Hz	MAX ABSORBED POWER	14 kW	DIMENSIONS (LxWxH)	95 x 49 x 68 cm
CURRENT RANGE IN DC	80 - 360 A	ABSORBED POWER AT 60%	8,4 kW	WEIGHT	101 kg
MAX CURRENT DC EN60974-1	325 @ 35 % A	POWER FACTOR(cosphi) (cosphi)	0,6		

ON REQUEST ACCESSORIES

GOUGING ACCESSORIES

802666 GOUGING KIT

ACCESSORIES/VARIOUS/SPARE PART

801093 MMA WELDING KIT 400A 50 MMQ 4+3M AX50

DESCRIPTION

MMA, rectified, electrode welding machine in direct current (DC).

Stepless regulation of welding current.

Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron and aluminium.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



CERTIFICATE