



- Direct current (DC) MMA electrode welding machine, 450A. Three-phase, 230/400V power supply. On wheels.
- Usable electrodes: rutile, basic, stainless steel, cast iron, aluminium, etc. up to 8 mm.
- Continuous adjustment of welding current.
- For heavy applications. With eyebolts for movement on the ship building site.
- Optional gouging kit.

TECHNICAL DATA

CODE	819055	DC CURRENT AT 60%	350 A	D.USABLE ELECTRODES IN DC	2 - 8 mm
THREEPHASE MAINS VOLTAGE	230 / 400 V	MAX NO LOAD VOLTAGE IN DC	70 V	PROTECTION DEGREE	IP22
MAINS FREQUENCY	50 / 60 Hz	MAX ABSORBED POWER	20 kW	DIMENSIONS (LxWxH)	100 x 54 x 76 cm
CURRENT RANGE IN DC	60 - 450 A	ABSORBED POWER AT 60%	16 kW	WEIGHT	170 kg
MAX CURRENT DC EN60974-1	410 @ 45 % A	POWER FACTOR(cosphi) (cosphi)	0,7		

ON REQUEST ACCESSORIES

GOUGING ACCESSORIES

802666 GOUGING KIT

ACCESSORIES/VARIOUS/SPARE PART

801106 MMA WELDING KIT 600A 70 MMQ 4+3M AX70

DESCRIPTION

MMA, rectified, electrode welding machine in direct current (DC).

Stepless regulation of welding current.

Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron and aluminium.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



CERTIFICATE