



- Alternating current (AC) MMA electrode welding machine, 330A. Three-phase, 400V power supply. On wheels.
- Usable electrodes: rutile up to 6 mm.
- Continuous adjustment of welding current.
- Thermostatic protection.

TECHNICAL DATA

CODE	817014	MAX CURRENT AC EN60974-1	250 @ 15 % A	POWER FACTOR(cosphi) (cosphi)	0,4
SINGLEPHASE MAINS VOLTAGE	230 V	AC CURRENT AT 60%	125 A	D.USABLE ELECTRODES AC	1,6 - 5 mm
TWO-PHASE MAINS VOLTAGE	400 V	MAX NO LOAD VOLTAGE IN AC	52 - 76 V	PROTECTION DEGREE	IP22
MAINS FREQUENCY	50 / 60 Hz	MAX ABSORBED POWER	9 kW	DIMENSIONS (LxWxH)	69 x 39 x 48 cm
CURRENT RANGE IN AC	45 - 250 A	ABSORBED POWER AT 60%	3,5 kW	WEIGHT	37 kg

ON REQUEST ACCESSORIES

ACCESSORIES/VARIOUS/SPARE PART

801102 MMA WELDING KIT 250A 25 MMQ 3+2M AX25

DESCRIPTION

MMA stick electrode welding machine in alternating current (AC).

Stepless regulation of welding current.

With thermostatic protection.

The model has double secondary voltage for use also with basic and rutile electrodes.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



CERTIFICATE