



TECHNICAL DATA

| | | | | | |
|---------------------------|---------------------|----------------------------|---------------|-------------------------------|----------------------------|
| CODE | 816151 | MAX NO LOAD VOLTAGE IN DC | 60 V | EFFICIENCY | 89 % |
| SINGLEPHASE MAINS VOLTAGE | 230 V | MAX ABSORBED CURRENT | 38 A | POWER FACTOR(cosphi) (cosphi) | 0,7 |
| MAINS FREQUENCY | 50 / 60 Hz | ABSORBED CURRENT AT 60% | 22 A | D.USABLE ELECTRODES IN DC | 1,6 - 4 mm |
| CURRENT RANGE IN DC | 5 - 200 A | MAX ABSORBED POWER | 6 kW | PROTECTION DEGREE | IP23 |
| MAX CURRENT DC EN60974-1 | 200 @ 35 % A | ABSORBED POWER AT 60% | 3,3 kW | DIMENSIONS (LxWxH) | 42 x 18,2 x 29,2 cm |
| DC CURRENT AT 60% | 140 A | MOTOREGENER. MINIMUM POWER | 10 kW | WEIGHT | 7,28 kg |

DESCRIPTION

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST